



## MONEL<sup>®</sup> Filler Metal 67

**MONEL Filler Metal 67** is used for oxyacetylene, gas-tungsten-arc, gas-metal-arc, and submerged-arc welding of MONEL alloy 450 (70/30 Copper-Nickel) and other copper-nickel alloys. It is used for surfacing of steel if a barrier layer of Nickel Filler Metal 61 is first applied. If applied by the submerged-arc process, MONEL Filler Metal 60 can be used for the barrier layer. Submerged-arc welding with MONEL Filler Metal 67 is done with INCOFLUX 8 Submerged Arc Flux.

The copper-nickel weld metal has excellent resistance to corrosion in sea water, and is widely used for marine and desalination applications.

Dissimilar-welding applications for MONEL Filler Metal 67 are joints between MONEL alloys or Nickel 200 and copper-nickel alloys.

### Specifications

AWS A5.7 ERCuNi (UNS C71581)

ASME II, Part C, SFA-5.7, ERCuNi (UNS C71581)

ASME IX, F-No.34

\*BS 2901 (C18)

\*DIN 1733 SG-CuNi30Fe (2.0837)

\*(EN) ISO SCu 7158 (CuNi30)

\*Supply to these specifications available upon request

For manufacture to ASME III (NCA3800, NB2400), MIL, and other specifications please refer your inquiry to the Technical Department prior to order placement.

### Approvals

VdTUV 4528.00; 4529.00

Other approvals may be applicable. Please confirm details of current scope of approvals with the Technical Department prior to order placement.

Limiting Chemical Composition	Ni+Co..... 29.0-32.0		Si ..... 0.25 max.	
	C..... 0.04 max.		Ti ..... 0.20-0.50	
Mn ..... 1.0 max.		P ..... 0.02 max.		
Fe..... 0.40-0.75		Pb..... 0.02 max.		
S..... 0.01 max.		Others ..... 0.50 max.		
Cu ..... Remainder				

Minimum Mechanical Properties	Tensile Strength, psi		50,000
			MPa
	Elongation, (4d) %		30

Filler metals available on spool and in cut straight lengths in a variety of sizes selected from the following diameters:

### Available Product Forms

mm in	0.8 0.030	0.9 0.035	1.0 0.040	1.14 0.045	1.2 0.047	1.6 0.062	2.4 0.093	3.2 0.125
----------	--------------	--------------	--------------	---------------	--------------	--------------	--------------	--------------

Straight Lengths - 915 mm (36 in.) or 1000 mm (39 in.)